

Products | Fuel transfer equipment

Filters



Baldwin bulk diesel filter with drain

- Rating: Basic dirt filter
- Suitable for gravity feed (not recommended on pressure exceeding 0.4bar)
- Micron: 10
- Flow rate: 60L/min



GUD/FRAM CF. 1000 bulk diesel filter with drain

- Rating: Basic dirt filter
- Suitable for gravity feed (not recommended on pressure exceeding 0.4bar)
- Micron: 20
- Flow rate: 40L/min



G13 Gilbarco bulk/dispenser diesel/petrol filter

- Rating: Basic dirt filter
- Pressure: 3.5bar (recommended to use with electric pumps)
- Micron: 30
- Flow rate: 57L/min



Piusi bulk high flow diesel filter

- Rating: Basic dirt filter
- Pressure: 12bar (recommended to use with electric pumps)
- Micron: 10 or 20
- Flow rate: 100L/min



Gespsa suction or gravity flow bulk diesel filter with drain

- Rating: Efficient dirt and water separation (90% of water decanting)
- Micron: 5
- Flow rate: 105L/min



F18 Jerrycar bulk dispenser (diesel/petrol) dirt and water separation filter

- Rating: High efficient separation
- Pressure: 3.5bar (recommended to use with electric pumps)
- Micron: 30
- Flow rate: 94L/min



F17 Jerrycar bulk dispenser (diesel/petrol) dirt and water particle removal filter

- Rating: High efficient water removal with absorption media
- Pressure: 3.5bar (recommended to use with electric pumps)
- Micron: 30
- Flow rate: 94L/min



Cimtec bulk dispenser (diesel/petrol) dirt and water particle removal filter

- Rating: High efficient water removal with absorption media
- Pressure: 3.5bar (recommended to use with electric pumps)
- Micron: 30
- Flow rate: 94L/min



Donaldson P179075 hydraulic dirt and water particle removal filter

- Rating: High efficient water removal with absorption media
- Pressure: 55bar (recommended to use with electric pumps)
- Micron: Not rated
- Flow rate: 180L/min

Products | Fuel transfer equipment

Filters



Velcon/Parker (Aquacon) aviation dirt and water particle removal filter

- Available in spin on and removable cartridge
- Rating: Aviation approved with absorption media
- Pressure: 3.5bar (recommended to use with electric pumps)
- Micron: 0.5
- Flow rate: 75L/min



G15 strainer

- 1" BSP
- Flow rate: 120L/min



G14 strainer (static applications)

- 1" BSP
- Flow rate: 120L/min



Donaldson breather for storage tanks and trailers

- 1" BSP male
- Remove dust and moist